

IMAGINE SURFACES TEXTURE MIX

Technical Data Sheet

Our Imagine Surfaces Texture Mix is a highly developed blend of silica sands, state of the art additives and white Portland Cement specifically formulated to be used as a thin section decorative overlayment.

Imagine Surfaces Texture Mix creates a 1/8" surface coating that is over 3500 p.s.i. tensile strength. In many cases, Imagine Surfaces Texture Mix is stronger then the concrete to which it is applied.

Imagine Surfaces Texture Mix is used in conjunction with Imagine Surface Acrylic Additive. These products combined are designed as a "Deck" coating system and will withstand the physical demands that are necessary in this difficult environment. This product will not crack, chip or craze under normal conditions.

Physical properties:

Make-up:	Silica Sands, Additives, Calcium Carbonate and White Portland
	Cement
Color:	Tan
Odor:	Slight
U.V. Resistance	10,000 hrs.Q.U.V. – No Effect
Water Soak:	2000 hrs. – No Effect
Tensile Strength:	3500 to 3800 lbs.
Coverage:	50 to 100 sq. ft. per 50 lb. bag.
Application Temp.:	Surface must be above 50F.
	Keep from Freezing

Designed for Industrial use only.

READ M.S.D.S. BEFORE USE

KEEP AWAY FROM CHILDREN.